

ContainersealACP49

Acrylic **Sealer**



FEATURES

Containerseal ACP49 is a solvent based acrylic sealer that exhibits excellent adhesion over a variety of substrates.

Based on an acrylic polymer, **Containerseal ACP49** forms a film that is strong, flexible, extremely durable and highly resistant to moisture and UV degradation.

Containerseal ACP49 has been specifically formulated to penetrate deep into the substrate and provide a stable platform for subsequent coatings to adhere.

RECOMMENDED USES

Containerseal ACP49 is the perfect single pack choice for sealing difficult or porous surfaces, and may be used on the following substrates:

- Porous concrete
- Cement render
- Masonry and brick
- Roof tiles and slate surfaces
- Ferrous and nonferrous metals

SPECIFICATION DATA

Colour:	White	Volume Solids:	~40%
Density:	~0.91 g/cc	Dry Film Thickness:	20-30 μ DFT
Packaging:	20 litre	Wet Film Thickness:	50 - 75 μ WFT
Application:	Spray, brush or roller	Coverage:	16 m ² / litre @ 25 μ DFT
Cleanup:	Thinner EX179	Number of Coats:	1 - 2 coats
Storage:	Store under cool dry conditions away from heat and sources of ignition.	Touch Dry:	10 minutes @ 25°C
		Hard Dry:	3 - 4 hours @ 25°C

DIRECTIONS FOR USE

Ensure all surfaces are clean, dry, and free from contamination, including fungal or algal growth.

Containerseal ACP49 is best applied by spray, where an even finish is readily achieved.

Apply un-thinned, however **Containerseal ACP49** may be thinned 5 - 10% on exceptionally porous surfaces.

Application by brush may be used for small surfaces. Large surfaces can be coated using a short nap roller or short bristle broom.

Apply one even coat. If a second coat is required, allow 3 - 4 hours drying before recoating with it-self. Allow 24 hours drying before applying water-based acrylic topcoats.

Provide adequate natural ventilation during use. Wash equipment immediately after use with **Cameleon Thinner EX179**.

DO NOT apply if temperature is below 10°C or above 38°C or if relative humidity is >85% or rain is imminent.

Typical Specifications

Surface	*Preparation	System	Dry Film Build
Metal, brick, masonry, concrete, cement render, fibre cement, roof tiles and slate surfaces.	Make any repairs, sand, and ensure that surface is clean and free from dust, oils and other surface contaminants.	1. Containerseal ACP49 2. Everbrite Camcrylic or Rooftop (optional)	20 - 30µ 40 - 50µ

PRECAUTIONS

IMPORTANT! See the Cameleon Paints General Safety Data Sheet, Product label, and Material Safety Data Sheet (MSDS) for health and safety information prior to use.

CAMELEON PAINTS

Manufacturers of a complete range of quality paints

A Division of Red Fire Holdings PTY Ltd ABN 65 009 407 381
26 Paramount Drive, Wangara, Western Australia 6065
PO Box 1473, Wangara, Western Australia 6947
Telephone (+61) 8 9302 2577 Fax (+61) 8 9302 2578
email@cameleon.com.au
www.cameleon.com.au

Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.