

Lifetime

Scrubbable 100% Acrylic



FEATURES

Lifetime Scrubbable 100% Acrylic is a premium quality waterborne coating especially formulated as an interior finish for walls, ceilings and wood work.

Based on a 100% acrylic polymer, **Lifetime** provides exceptional strength, durability and flexibility.

The cured coating is completely scrubbable providing a decorative hard-wearing finish – especially important in areas where paint finishes can be easily marked.

RECOMMENDED USES

Lifetime is ideal for walls and ceilings in:

- Kitchens and dining areas
- Bedrooms
- Lounge and games rooms
- Bathrooms and laundries

Lifetime is also suitable for high traffic areas such as corridors and foyers, and is particularly useful in children's areas.

SPECIFICATION DATA

Generic Type:	Acrylic	Volume Solids:	~ ⁽¹⁾ 38%
Finish:	Satin, Low Sheen and Matt	Dry Film Thickness:	40 - 50µ DFT
Colour:	Cameleon Std pastel colour range, custom colours upon request	Wet Film Thickness:	⁽¹⁾ 110 - 140µ WFT
Density:	⁽¹⁾ ~1.33 g/cc	Coverage:	⁽¹⁾ 14 - 16 m ² / litre
Packaging:	1,2,4, 10 litre.	Number of coats:	2 - 3 coats for optimum coverage
Application:	Brush, roller or airless spray.	Touch Dry:	20 - 30 minutes
Thinner:	Water	Dry to Recoat:	2 hours
Cleanup:	Water	Storage:	Store under cool dry conditions.

⁽¹⁾ Based on Satin White, may vary between sheen levels and colours

DIRECTIONS FOR USE

Ensure surfaces are clean, dry and free from dust, oil, grease or other surface contamination. It is advisable to thoroughly wash pre-painted surfaces with sugar soap and water and allowing to dry before painting with **Lifetime**.

Kalsomine surfaces should be thoroughly scrubbed and sealed with Cameleon **Unibind** prior to top coating with **Lifetime**.

Apply un-thinned, however, 5 – 10% water may be added to the first coat to aid sealing of porous surfaces.

DO NOT apply if temperature is below 10°C, or relative humidity is above 85%.

When cleaning **Lifetime use soft-bristled brush, warm water and soft soap. Dry with a soft cloth. DO NOT expose freshly painted surfaces to excessive steam or humidity for the first 48 hours.*

Typical Specifications

Surface	Preparation	System	Dry Film Build
New Plaster, plasterboard and fibre sheeting	Ensure the surface is clean, dry, and free from oil, grease or other surface contaminants.	1. Lifetime (thinned 5-10% with water) 2. Lifetime	40 - 50µ (²)80 - 100µ
Porous powdery surfaces (Kalsomine)	Thoroughly scrub the surface to remove any loose material. Ensure the surface is clean and dry and free from any surface contaminants	1. Unibind 2. Lifetime	40 - 50µ (²)80 - 100µ
New Gyprock	Ensure the surface is clean, dry, and free from oil, grease or other surface contaminants.	1. Acritec or Gyptec 2. Lifetime	40 - 50µ (²)80 - 100µ
New Wood	Ensure adequate dusting after any sanding.	1. Timbaprime 2. Galactic (if required) 3. Lifetime	40 - 50µ 50 - 75µ (²)80 - 100µ

(²) 2 coats at 40 - 50 µ DFT per coat recommended.

PRECAUTIONS

See the Cameleon Paints General Safety Data Sheet, Product label, and Material Safety Data Sheet (MSDS) for health and safety information prior to use.

CAMELEON PAINTS

Manufacturers of a complete range of quality paints

A Division of Red Fire Holdings PTY Ltd ABN 65 009 407 381
26 Paramount Drive, Wangara, Western Australia 6065
PO Box 1473, Wangara, Western Australia 6947
Telephone (+61) 8 9302 2577 Fax (+61) 8 9302 2578
email@cameleon.com.au
www.cameleon.com.au

Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.