

Splendor

Washable Acrylic Vinyl



FEATURES

Splendor is a premium quality water borne acrylic vinyl coating, formulated to provide a tough, hard finish for both interior and exterior applications.

Splendor is available in a variety of sheen levels, all of which dry to a smooth easily washable finish. Matt finish is particular suitable for gyrock ceilings and walls.

RECOMMENDED USES

Splendor is the perfect choice for ceilings and walls where a hard washable coating is required for easy maintenance. It is ideal for interior living areas and external walls, including the following:

- Bedrooms, bathrooms and wet areas.
- Kitchens and living areas
- Exterior walls, eaves and timber

SPECIFICATION DATA

Generic Type:	Vinyl Acrylic.	Volume Solids:	~37% ⁽¹⁾
Finish:	Matt, Low Sheen and Satin.	Dry Film Thickness:	30 – 40µ DFT
Colour:	White. <i>(Full Cameleon Colour Range)</i>	Wet Film Thickness:	80 - 110µ WFT
Density:	~1.33 g/cc ⁽¹⁾	Coverage:	9 - 12 m ² / litre ⁽¹⁾
Packaging:	6 and 10 litre.	Number of coats:	2 coats optimum
Application:	Brush, Roller and spray	Touch Dry:	30 minutes
Thinner:	Water	Dry to Recoat:	2 hours
Cleanup:	Water	Hard Dry:	8 hours.
		Storage:	Store under cool dry conditions.

⁽¹⁾ For Satin White, may vary depending on colour.

DIRECTIONS FOR USE

Ensure all surfaces are clean, dry, and free from oil, grease and dust. Repair and sand surface removing any loose or peeling paint. Spot prime bare surfaces prior to top coating.

Kalsomine coated surfaces should be thoroughly scrubbed and primed with Cameleon **Unibind** prior to top coating.

Apply un-thinned, but the maximum addition of 10% Water may be added to the first seal coat on absorbent surfaces.

Stir well and ensure colour (if tinted) is as required before use. Provide adequate natural ventilation during use. Wash equipment immediately after use with water.

DO NOT apply if temperature is below 10°C, or relative humidity is above 85%.

Typical Specifications

Surface	Preparation	System	Dry Film Build
Kalsomine Surfaces	Thoroughly scrub the surface to remove any loose material. Allow to dry, ensuring the surface is free from any surface contamination.	1. Unibind 2. Splendor 3. Splendor	40 - 50µ 30 - 40µ 30 - 40µ
Timber	Remove any loose material, repair and sand if required. Ensure surfaces are clean, dry and free from oils, grease or other surface contaminants.	1. Timbaprime (spot prime) 2. Galactic 3. Splendor 4. Splendor	50µ 50 - 75µ 30 - 40µ 30 - 40µ
Plasterboard	Ensure surfaces are clean, dry and free from oils, grease or other surface contaminants.	1. Plastershield 2. Splendor 3. Splendor	30 - 40µ 30 - 40µ 30 - 40µ
Gyprock, masonry and brick, cement render	Ensure surfaces are clean, dry and free from oils, grease or other surface contaminants.	1. Acritec 2. Splendor 3. Splendor	50µ 30 - 40µ 30 - 40µ
New and weathered Galvanising	Thoroughly scrub the surface to remove any white corrosion products and surface contamination (oil, grease etc). Prepare substrate to SSPC-SP-1.	1. Galvabond 2. Splendor 3. Splendor	25 - 30µ 30 - 40µ 30 - 40µ

PRECAUTIONS

See the Cameleon Paints General Safety Data Sheet, Product label, and Material Safety Data Sheet (MSDS) for health and safety information prior to use.

CAMELEON PAINTS

Manufacturers of a complete range of quality paints

A Division of Red Fire Holdings PTY Ltd ABN 65 009 407 381
26 Paramount Drive, Wangara, Western Australia 6065
PO Box 1473, Wangara, Western Australia 6947
Telephone (+61) 8 9302 2577 Fax (+61) 8 9302 2578
email@cameleon.com.au
www.cameleon.com.au

Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.