

Flexituff

AcrylicCementAdditive



FEATURES

Flexituff Cement Additive is an acrylic polymer for two pack cement based formulations. The addition of **Flexituff**, replacing water in the cement / sand slurry, increases the strength, flexibility and adhesion of the cement based product.

This addition enhances the properties, and increases the areas of use of conventional and light-weight renders, where lack of adhesion and flexibility can cause problems.

Flexituff added to render allows application onto walls previously painted with acrylic without having to remove the coating.

Furthermore, the addition of **Flexituff** is highly beneficial in waterproofing systems, patching and repair mortars, underlayments and commercial flooring.

Renders containing **Flexituff** can be easily coated with textured wall coatings or conventional acrylic paints.

RECOMMENDED USES

Flexituff is ideal for use in the following applications:

- Renders
- Patching and mortar compounds
- Waterproofing systems

As a cement additive wherever improved adhesion, flexibility, strength and durability are desired.

SPECIFICATION DATA

Colour:	Opaque	Addition level:	0 – 100% of water
Volume Solids:	43%	Minimum Render Recoat time:	24 hours
Density:	~1.05g/cc	Minimum Flooring Recoat time:	18 - 24 hours ⁽¹⁾
Packaging:	10 litre, 20 litre		
Cleanup:	Water		
Storage:	Store under cool dry conditions		

⁽¹⁾Depending on thickness

DIRECTIONS FOR USE

If application is over an existing paint or coating, ensure that the surface is thoroughly clean by high pressure water blasting, and allowed to dry.

For optimum results use **Flexituff** undiluted as a direct replacement for the water component, especially where used to provide a bond onto painted or pre-coated surfaces.

If used as a flex additive, dilute **Flexituff** 10% with water prior to addition to the cement / sand slurry, and apply the cement slurry as normal.

DO NOT apply if rain is imminent!

Typical Specifications

Use	Preparation	System
Prepainted acrylic surfaces	Thoroughly clean the surface by high pressure water blasting and allow to dry.	1. Cement render with undiluted Flexituff.
Flexibility additive		1. Cement render with Flexituff diluted 10% with water

PRECAUTIONS

IMPORTANT. See the Cameleon Paints General Safety Data Sheet, Product label, and Material Safety Data Sheet (MSDS) for health and safety information prior to use.

CAMELEON PAINTS

Manufacturers of a complete range of quality paints

A Division of Red Fire Holdings PTY Ltd ABN 65 009 407 381
26 Paramount Drive, Wangara, Western Australia 6065
PO Box 1473, Wangara, Western Australia 6947
Telephone (+61) 8 9302 2577 Fax (+61) 8 9302 2578

email@cameleon.com.au

www.cameleon.com.au

Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.