

# Ground MarkingPaint



## FEATURES

**Ground Marking Paint** is a water-borne acrylate emulsion specifically designed for the general ground marking.

**Ground Marking Paint** combines a unique blend of pigments and extenders to produce a highly visible and durable ground marking.

Being water-borne, **Ground Marking Paint** will not harm grass or the soil, is simple and safe to apply, and dries quickly to a uniform flat finish.

Ground Marking Paint is available in bright white, or a range of highly visible bright standard colours.

## RECOMMENDED USES

**Ground Marking Paint** is specifically designed for ground marking, for soil or grassed areas and is suitable for marking tree.

It is suitable for use in

- Agriculture
- Mining Industry
- Sporting Fields
- Construction Industry

## SPECIFICATION DATA

<b>Generic Type:</b>	Water Based Acrylic	<b>*Volume Solids:</b>	22-24%
<b>Finish:</b>	Flat	<b>Dry Film Thickness:</b>	50µ.
<b>Colour:</b>	White / Bright Colours	<b>Wet Film Thickness:</b>	250 µ.
<b>Density:</b>	1.30 ± 0.04 g/cc	<b>**Coverage:</b>	8-12 m <sup>2</sup> / litre
<b>Packaging:</b>	10, 20 litre.	<b>Number of coats:</b>	1 - 2
<b>Application:</b>	Back Pack Spray Ground Marking Applicators, Brush or Airless Spray	<b>Touch Dry:</b>	20 minutes
<b>Thinner:</b>	Water	<b>Dry to Recoat:</b>	30 – 40 minutes
<b>Cleanup:</b>	Water	<b>Storage:</b>	Store under cool dry conditions

\*Volume Solids varies with Colour

\*\*Coverage varies with porosity of ground

## DIRECTIONS FOR USE

Volume Solids varies with colour

Coverage varies with porosity of ground

May be applied by standard grass marking applicators, but also suitable for airless spraying or brushing. Back Pack applicators can be used.

Apply un-thinned. A maximum of 25% water may be added if required by method application.

Ensure that the grass is relatively dry. **DO NOT** apply if rain or bad weather is imminent.

**DO NOT apply if temperature is below 10°C, or relative humidity is above 85%.**

### Typical Specifications

Surface	Preparation	System	Dry Film Build
Grass surfaces	Ensure that grass is relatively dry. Do Not apply if rain or bad weather is imminent.	1. Ground Marking Paint	50µ
		2. *Ground Marking Paint	50µ

*\* Apply a second coat if required to achieve full coverage.*

## PRECAUTIONS

See the Cameleon Paints General Safety Data Sheet, Product label, and Material Safety Data Sheet (MSDS) for health and safety information prior to use.

## CAMELEON PAINTS

### Manufacturers of a complete range of quality paints

A Division of Red Fire Holdings PTY Ltd ABN 65 009 407 381  
26 Paramount Drive, Wangara, Western Australia 6065  
PO Box 1473, Wangara, Western Australia 6947  
Telephone (+61) 8 9302 2577 Fax (+61) 8 9302 2578  
[email@cameleon.com.au](mailto:email@cameleon.com.au)  
[www.cameleon.com.au](http://www.cameleon.com.au)

### Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.