

TexasModified

AcrylicTexturedMembrane



FEATURES

Texas Modified is a premium quality acrylic textured coating, modified from standard Texas, for use in special applications.

The main feature of **Texas Modified** is it's ability to bridge fine cracks whilst producing a smooth, fine textured finish which is strong, flexible, durable and washable.

Specifically formulated for interior use where cracks have appeared on plaster walls, **Texas Modified** will dry to a low sheen finish, and is available in a large range of colours.

Texas Modified may also be used for exterior application where a more subtle textured finish is desired than the traditional standard texture coatings.

RECOMMENDED USES

Due to its unique properties, **Texas Modified** is ideal for bridging fine cracks both interior and exterior, and is suitable for application to the following substrates:

- Masonry and cement render
- Concrete and plaster
- Cement fibre sheeting
- Brick and plaster
- Gyprock
- Brick

SPECIFICATION DATA

Generic Type:	Water borne Acrylic.	Volume Solids:	~41%.
Finish:	Low sheen	Dry Film Thickness:	*150 – 200 µ.
Colour:	White	Wet Film Thickness:	*370 - 490 µ.
Density:	1.36 ± 0.04 g/cc	Coverage:	*4 - 6 m ² / litre
Packaging:	10 litre.	Number of coats:	2 coats optimum
Application:	Roller and airless spray	Touch Dry:	2 - 4 hours
Thinner:	Water	Dry to Recoat:	12 hours
Cleanup:	Water.	Hard Dry:	8 - 10 hours.
		Storage:	Store under cool dry conditions.

** Note: Due to the texture effect creating a unique "profile", Coverage, WFT and DFT should be taken as a guide only.*

DIRECTIONS FOR USE

Ensure all surfaces are clean, dry, and free from oil, grease and dust. The surface should be firm and solid, with loose material removed and large cracks or holes filled. Very smooth or porous surfaces should be primed with Cameleon **Acritec**; or alternatively, apply a prime coat of **Texas Modified** thinned 5 - 10% with water as a seal coat.

Texas Modified is best applied un-thinned, using a medium nap quality roller which will produce uniform thickness and appearance. A fine textured roller can be used to produce a subtle textured effect. When applying by roller, ensure the **Texas Modified** is "laid off" in one direction (downwards) to produce a uniform pattern. Roll closely to the brushed cut-in areas. **Texas Modified** may also be applied by airless spray.

Stir well and ensure colour (if tinted) is as required before use. Provide adequate natural ventilation during use. Wash equipment immediately after use with water.

DO NOT apply if temperature is below 10°C, above 37°C, or relative humidity is above 85%.

Typical Specifications

Surface	Preparation	System	Dry Film Build
Porous and previously painted surfaces	Surfaces should be sanded with all loose flaking paint removed. Ensure that surfaces are clean, dry and dust free.	1. Acritec 2. Texas Modified 3. Texas Modified	50µ 150 - 200µ 150 - 200µ
Masonry, cement render, brick	Ensure that surfaces are clean, dry and dust free.	1. Texas Modified 2. Texas Modified	100 - 150µ 150 - 200µ
Kalsomine coated surfaces	Thoroughly scrub the surface to remove any loose material. Ensure that the surface is clean, dry and dust free.	1. Unibind 2. Texas Modified 3. Texas Modified	50µ 150 - 200µ 150 - 200µ

PRECAUTIONS

See the Cameleon Paints General Safety Data Sheet, Product label, and Material Safety Data Sheet (MSDS) for health and safety information prior to use.

CAMELEON PAINTS

Manufacturers of a complete range of quality paints

A Division of Red Fire Holdings PTY Ltd ABN 65 009 407 381
26 Paramount Drive, Wangara, Western Australia 6065
PO Box 1473, Wangara, Western Australia 6947
Telephone (+61) 8 9302 2577 Fax (+61) 8 9302 2578
email@cameleon.com.au
www.cameleon.com.au

Disclaimer

This is not a specification, and all the information is given in good faith. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated, the manner of use and whether there is any infringement of patents is the sole responsibility of the user. The manufacturer does not assume any liability in connection with the use of the product relative to coverage, performance or injury. For application in special conditions, consult the manufacturer for detailed recommendations.