

Section 1 PRODUCT IDENTIFICATION				
Product Name:	Campoxy SFE Sealer Part B			
Synonyms:	Campoxy SFE Sealer hardener			
Recommended Use:	Curing agent for Campoxy SFE Sealer Part A			
Supplier Information:	Cameleon Coatings 26 Paramount Drive Wangara 6055 Phone:(08) 9302 2577 www.cameleon.com.au Emergency Phone: 0413 610 147 (24 hours)			

## Section 2 HAZARD IDENTIFICATION

Hazard Classification:

DANGEROUS GOODS according to the criteria of the ADG code

HAZARDOUS CHEMICAL according to the criteria of Safe Work Australia

Eye damage/Irritation, Category 1

Skin corrosion / Irritation, Category 1A

Specific Target Organ Toxicity (single exposure), Category 3 (respiratory tract irritation)

Acute Toxicity - Inhalation, Category 4

Acute Toxicity - Oral, Category 4

Sensitisation - Skin, Category 1

Acute aquatic toxicity, Category 2

Chronic aquatic toxicity, Category 2

Label elements:

**Pictograms** 



IRRITANT



**ENVIRONMENT** 



CORROSIVE

Signal Word: **DANGER** 

Hazard Statements:

H318 Causes serious eye damage

H314 Causes severe skin burns and eye damage

H335 May cause respiratory irritation

H332 Harmful if inhaled

H302 Harmful if swallowed

H317 May cause an allergic skin reaction

H411 Toxic to aquatic life with long lasting effects

Product Name: Campoxy SFE Sealer Part B Issued: September 2016 Page 1 of 7



Precautionary Statements:

**GENERAL** 

P101 If medical advice is needed, have product container or label at hand

P102 Keep out of reach of children

P103 Read label before use

**PREVENTATIVE** 

P260 Do not breathe mists/vapour/spray

P264 Wash skin thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P271 Use only outdoors or in a well-ventilated area

P272 Contaminated work clothing should not be allowed out of the workplace

P273 Avoid release to the environment

P280 Wear protective gloves/eye protection/face protection

RESPONSE

P301+P312 IF SWALLOWED: Call a Poison Centre or doctor if you feel unwell

P301+P330 IF SWALLOWED: rinse mouth. DO NOT induce vomiting

+P331

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P303+P361+ IF ON SKIN (or hair): Take off contaminated clothing and wash before reuse

P353 Rinse skin with water/shower

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing

P305+P351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

+P338 lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell

P314 Get medical advice/attention if you feel unwell

P331 Do NOT induce vomiting

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P363 Wash contaminated clothing and wash before reuse

**STORAGE** 

P403+P233 Store in a well-ventilated place. Keep container tightly closed

P405 Store locked up

DISPOSAL

P501 Dispose of contents/container in accordance with local regulations

Section 3 COMPOSITION				
Ingredient	CAS Number	Proportion		
Benzyl alcohol	100-51-6	>35%		
4,4'-methylenebis(cyclohexylamine)	e) 1760-71-3			
Other Non-Hazardous Materials to 100%				

Proportion is % weight per weight

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS)

Product Name: Campoxy SFE Sealer Part B Issued: September 2016 Page 2 of 7



# Section 4 FIRST AID MEASURES

Poisons Information Centres in each State capital city can provide additional assistance for scheduled poisons.

**Ingestion**: Do **NOT** induce vomiting. Never give anything by mouth to an unconscious person. Prevent aspiration of vomit. Rinse mouth thoroughly with water and contact a Poisons Information Centre. Urgent hospital treatment is likely to be needed.

**Eye Contact:** Immediately irrigate with copious quantities of water for at least 1 hour with eyelids held open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Seek medical advice. Take special care if the person is wearing contact lenses.

**Skin Contact:** Immediately wash contaminated skin with lukewarm, gently flowing water for at least 1 hour. DO NOT INTERRUPT FLUSHING. Remove contaminated clothing and wash before re-use. Destroy contaminated leather apparel. Strongly basic ingredients tend to penetrate the skin and so need longer rinsing than other substances. Seek Medical Attention.

**Inhalation:** If breathing has stopped or is laboured, give assisted respiration. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Move to fresh air.

**Most important symptoms/effect, acute and delayed:** Aggravated medical conditions: Eye disease, skin disorders and allergies. Asthma. Neurological disorders. Liver disorders.

### Section 5 FIRE FIGHTING MEASURES

### Specific Hazards:

May generate toxic, irritating or flammable combustion products. Contact of liquid with skin must be prevented. Sudden reaction and fire may result if product is mixed with an oxidising agent. Incomplete combustion may form carbon monoxide. May generate ammonia gas. May generate toxic nitrogen oxide gases.

### Fire Fighting Advice:

On burning this product may emit toxic nitrogen oxide gases. May generate ammonia gas. Personnel in vicinity and down-wind should be evacuated. Fire fighters to wear self-contained breathing apparatus, butyl rubber boots, gloves, and body suit if risk of exposure to vapour or decomposition products.

#### Suitable Extinguishing Media:

Alcohol-resistant foam, carbon dioxide, dry chemical, dry sand, limestone powder

## Section 6 ACCIDENTAL RELEASE MEASURES

Clear area of all unprotected personnel. Remove all possible sources of ignition. Product is slippery when spilt. Avoid accidents and clean up immediately.

Wear protective equipment to prevent skin, eye contamination or inhalation of vapours. Use self-contained breathing apparatus and chemical protective clothing. Evacuate personnel to safe areas,

Contain immediately – prevent run-off into drains and waterways. Use absorbent (soil, sand, or other inert material). Collect and seal in properly labelled containers for disposal per local regulations. If contamination of sewers or waterways has occurred advise the local emergency services.

Product Name: Campoxy SFE Sealer Part B Issued: September 2016 Page 3 of 7



### Section 7 HANDLING AND STORAGE

### Precautions for safe handling

Use only in well-ventilated areas. Avoid breathing vapours and/or aerosols. Avoid contact with skin and eyes. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Use personal protective equipment. When using, do not eat, drink or smoke.

### Conditions for safe storage, including any incompatibilities

Do not store near acids. Keep containers tightly closed in a cool, dry, well-ventilated place. Product may partially freeze with extended exposure to cold temperatures, resulting in crystallisation, haziness or separation. If this occurs, product should be warmed to 38-60 deg C for one hour and stirred until clear.

Do not stir near acids. Keep from freezing.

## Section 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

### **National Exposure Limits.**

No value has been assigned for this specific product by the National Occupational Health and Safety Commission (NOHSC) Worksafe Australia

**Engineering Controls:** Provide readily accessible eye wash stations and safety showers. Ensure adequate ventilation; keep containers closed when not in use.

**Respiratory Protection:** Use with adequate ventilation – if inhalation risk exists then wear an organic vapour / particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Eye Protection: Full face shield with Chemical Goggles underneath. Chemical resistant goggles must be worn.

Hand Protection: Neoprene gloves. PVC disposable gloves. Nitrile rubber. Impervious gloves.

The breakthrough time of the selected glove(s) must be greater than the intended use period.

**Body Protection:** Slicker suits. Impervious clothing. Full rubber suit (rain gear). Rubber or plastic boots. **Special Protective Measures:** Discard contaminated leather articles. Provide readily accessible eye wash stations and safety showers. Wash at the end of each work shift and before eating, smoking or using the toilet. Remove contaminated clothing.

## **Section 9 PHYSICAL PROPERTIES**

Appearance: Colourless mobile liquid

Solubility: Insoluble in water

Odour:	Ammoniacal	Density @ 20°C:	~1.03 kg/lt	
pH:	Alkaline	Flash point & Method:	~ 112°C Closed Cup	
Vapour Pressure 20°C (mm Hg):	<10.3 kPa	Upper Explosive Limit (UEL):	NAV	
Vapour Density (Air = 1)	NAV	Lower Explosive Limit (LEL):	NAV	
Initial Boiling Point & Range °C:	~207	Ignition Temperature °C:	NAV	
Freezing Point °C:	NAV	Percent Volatiles (by weight):	0%	

NAP = Not Applicable, NAV = Not Available

Product Name: Campoxy SFE Sealer Part B Issued: September 2016 Page 4 of 7



# Section 10 STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions.

**Incompatible Materials:** Reactive metals (e.g. sodium, calcium, zinc, etc.) Materials reactive with hydroxyl compounds. Sodium hypochlorite. Organic acids. Mineral acids. Oxidising agents.

**Hazardous Decomposition Products:** Nitric acid. Ammonia. Oxides of nitrogen. Nitrogen oxides can react with water vapours to form corrosive nitric acid. Carbon monoxide. Carbon dioxide (CO2). Aldehydes. Flammable hydrocarbon fragments.

**Possibility of hazardous reactions:** Reaction with peroxides may result in violent decomposition of peroxide possibly creating an explosion. Product slowly corrodes copper, aluminium, zinc and galvanised surfaces.

## Section 11 TOXICOLOGICAL INFORMATION

Acute toxicity:	LD50 Oral (rat) > 2000 mg/kg			
Addit toxioity.	LD50 Dermal (rabbit) > 2110 mg/kg			
Skin	Causes skin burns. If absorbed through the skin, may cause central nervous			
corrosion/irritation:	· · · · · · · · · · · · · · · · · · ·			
corrosion/irritation:	system effects such as headache, nausea, dizziness, confusion, breathing			
	difficulties			
Serious eye	Causes eye burns. May cause blindness. Severe eye irritation			
damage/irritation:				
Respiratory or skin	May cause sensitisation of susceptible persons by skin contact			
sensitisation:				
Germ cell	Not mutagenic			
mutagenicity:				
Carcinogenicity:	Not expected to be carcinogenic.			
Reproductive	Not expected to be human reproductive toxicant.			
toxicity:				
Inhalation	Harmful if inhaled and may cause delayed lung injury. Can cause severe eye,			
	skin and respiratory tract burns. Risk of serious damage to the lungs by			
	inhalation. May cause nose, throat and lung irritation. Inhalation of aerosol			
	may cause irritation to the upper respiratory tract. May cause central nervous			
	system effects such as headache, nausea, dizziness, confusion, breathing			
	difficulties. Severe cases of overexposure can result in respiratory failure.			
	amiliani de la company de la c			
Ingestion:	If ingested, severe burns of the mouth and throat as well as a danger of			
	perforation of the oesophagus and the stomach.			
	1			

Product Name: Campoxy SFE Sealer Part B Issued: September 2016 Page 5 of 7



## Section 12 ECOLOGICAL INFORMATION

#### **Ecotoxicity**

No data available on the product

## Persistence and degradability

Data not available

#### Bioaccumulative potential

Data not available

#### Mobility in soil

Data not available

#### Other adverse effects

Data not available.

## Section 13 DISPOSAL CONSIDERATIONS

Dispose of waste according to applicable local, state and federal regulations.

The product should not be allowed to enter drains, water courses or the soil. Dispose of this material and it's container in a safe way

# Section 14 TRANSPORT INFORMATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG7 Code) for transport by road or rail.

UN Number:	3066	HAZCHEM:	2X
UN Proper Shipping Name:	PAINT RELATED MATERIAL	Packaging Group:	II
Class and Sub Risk:	8 Corrosive Liquid		

Special Precautions: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1) in bulk. poisonous gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2) and radioactive substances (Class 7), however, exemptions may apply.

## Section 15 REGULATORY INFORMATION

Hazardous according to Safe Work Australia

Poisons Schedule (Australia): \$5

Issued: September 2016 Product Name: Campoxy SFE Sealer Part B Page 6 of 7



# **Section 16 OTHER INFORMATION**

Date of preparation: September 2016

Version 1.04

#### General:

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular, how to safely handle and use the product in the work-place.

Since Cameleon Coatings cannot anticipate or control the conditions under which this product may be used or handled, each user must, prior to using or handling this product, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is required to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers, and is also available from the company upon request.

Issued: September 2016 Product Name: Campoxy SFE Sealer Part B Page 7 of 7